

爆発__予防

番号	英 語	日本語訳
1	Above [N1]° C use a closed system and ventilation.	[N1]°C以上では、密閉系および換気
2	Above [N1]° C use a closed system, ventilation and explosion-proof electrical equipment.	[N1]°C以上では、密閉系、換気、および防爆型電気設備
3	Closed system, dust explosion-proof electrical equipment and lighting.	密閉系、粉塵防爆型電気設備および照明設備
4	Closed system, ventilation, explosion-proof electrical equipment and lighting.	密閉系、換気、防爆型電気設備および照明設備
5	Do NOT expose to friction or shock.	摩擦や衝撃を与えない
6	Do not expose to heat and keep wet with at least 30% water.	熱に暴露させず、少なくとも水分30%の湿潤状態を保つ
7	Do NOT expose to heat, friction or shock.	熱、摩擦および衝撃を与えない
8	Do NOT use compressed air for filling, discharging, or handling.	充填、取り出し、取り扱い時に圧縮空気を使用してはならない
9	Flame arrester to prevent flash-back from burner to cylinder.	燃焼器から圧力容器への逆火防止器
10	NO contact with incompatible materials.	混触危険物との接触禁止
11	NO contact with strong oxidizing agents.	強力な酸化剤との接触禁止
12	Prevent build-up of electrostatic charges (e.g., by grounding) if in liquid state.	液状であれば、帯電を防ぐ(例えばアースを使用)
13	Prevent build-up of electrostatic charges (e.g., by grounding).	帯電を防ぐ(例えばアースを使用)
14	Prevent deposition of dust.	粉塵の堆積を防ぐ
15	PREVENT DISPERSION OF DUST.	粉塵の拡散を防ぐ
16	Prevent warming above [N1]° C.	[N1]°C以上の加温を防ぐ
17	See Chemical Dangers	「化学的危険性」参照
18	See Notes.	「注」参照
19	Use non-sparking handtools.	火花防止工具を使用する
20	Vapours will be uninhibited and may polymerize in exhaust or ventilation facilities with risk of breakdown.	故障の危険性のある排気または換気設備では、蒸気は重合する可能性がある